



INDIA GLUE & FERTILIZER MILL

TECHNICAL DATA SHEET

HIDE GLUE IN GROUND FOAM

GRADE	200 GEL	250 GEL	350 GEL	400 GEL
PHYSICAL APPEARANCE	FLAKES	FLAKES	FLAKES	FLAKES
COLOUR	LIGHT BROWN	LIGHT BROWN	LIGHT BROWN	Light Brown
ODOUR	NORMAL	NORMAL	NORMAL	NORMAL
MINIMUM GEL STRENGTH \pm 10% of 12.5% SOLUTION DETERMINED AT 10 °C (GMS)	200 GEL	250 GEL	350 GEL	400 GEL
CLARITY	OPAQUE	OPAQUE	OPAQUE	OPAQUE
Ph	6.8	6.8	6.5	6.5
MINIMUM VISCOSITY (cps/mps) OF A SIMILAR SOLUTION DETERMINED AT 60 °C	110	125	165	190
MAXIMUM MOS. CONTENTS %	8%	8%	7%	7%
KEEPING QUALITY (MINIMUM)	72 Hrs.	72 Hrs.	72 Hrs.	72 Hrs.
FOAM	CONTROLLED	CONTROLLED	CONTROLLED	CONTROLLED

APPLICATION

- Hide Glue of 350 & 400 Gel strength is widely used in coated abrasive (Emery Paper, Rolls, Discs, Etc.) Rayon Yarn Sizing.]
- Hide Glue of 200 & 250 Gel Strength is widely used in Oil Bound Distemper, Joinery works (Paper Cartons, Tubes, Cones, Furniture, Pencils) Safety Matches (for head and side composition) Gum paper and sizing of paper.

DOSAGE

- Depending on the Customer used and extent to Strength required.

PACKING

- Hide Glue is packed in 25 Kgs. HDPE woven bags with a polythene liner inside.

STORAGE

Its storage stability is good enough provided it is stored.

- In a cool and dry place.



INDIA GLUE & FERTILIZER MILL

HANDLING

⇒ Hide Glue is substantially free from handling problems. Avoid creating dusty conditions because of possibility of respiratory.

OUR STATEMENT

⇒ The statements made in the above documents are correct to the best of our knowledge and belief. India Glue & Fertilizer Mill gives no warranty as to their accuracy and will not be responsible for any loss or expenses arising from use of these products.

OUR OFFICE

REGD. & EXORT OFFICE	FACTORY	REGIONAL OFFICE
106, Bhagat Singh Chowk, Hanumangarh Jn. – 335512 Rajasthan (INDIA) Tel.: +91-1552-265677,263210 FAX: +91-1552-261110 Email: amit_khadgawat@hotmail.com Website: www.khadgawatsgroup.com	A-40, Industrial Area, Hanumangarh Jn. – 335512 Rajasthan (INDIA) Tel.: +91-1552-260210 Fax: +91-1552-251110	